

Code: AXD-200-DG

UNIVERSAL WIRELESS DETECTOR **AXD-200-DG** ABAX/ABAX2 SATEL

Net: 168.00 PLN Gross: 206.64 PLN

The AXD-200-DG wireless detector can work in one of the 7 modes, which makes it an extremely universal device. Depending on your needs, the device can be configured as: two-channel magnetic detector, magnetic detector with roller shutter (for wired sensor), shock detector with reed switch, position sensor, temperature detector or water flood detector (FPX-1 external probe required - available separately). The AXD-200-DG supports the other devices compatible with wireless ABAX/ABAX2 system.



SPECIFICATION

Support:	ABAX/ABAX2
Alarm signaling:	Signal to control panel
Frequency band:	868 MHz ... 868.6 MHz
Radio communication range (at open area):	<ul style="list-style-type: none">• ~ 500 m @ ABAX,• ~ 2000 m @ ABAX2
Battery:	CR123A 3 V - 3.0 V (included)
Backup time:	~ 2 years
Main features:	<ul style="list-style-type: none">• Operation modes :<ul style="list-style-type: none">- Magnetic detector- Dual channel magnetic detector- Magnetic detector with roller shutter input - Input to an additional wired detector- Shock and magnetic detector - Detection of shocks and vibrations associated with attempts to force a door or window- Reorientation detector - Detecting a change in position of an object- Temperature sensor - Temperature measurement in the range: -10°C ... +55°C, Two programmable temperature thresholds (upper and lower)- Water flood detector - The required FPX-1 probe is available separately• Tamper detection - opening the enclosure, removing from mounting surface• Remote configuration• Remote update of module software• The LED to indicate violations in test mode, easy start-up and later maintenance of the system
Operation temp:	-10 °C ... 55 °C
Color:	Dark graphite
Weight:	0.023 kg

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions:	20 x 102 x 23 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION

Front view:



Internal view of the housing:



Mounting side view:



In the kit:

