

Code: ADD-200

WIRELESS DUSK AND TEMPERATURE DETECTOR **ADD-200** ABAX2 SATEL

Net: **45.68 EUR** Gross: **45.68 EUR**



ADD-200 detects changes of light intensity (dusk detector) and temperature (temperature detector).

The ADD-200 supports the other devices compatible with wireless ABAX2 system.

SPECIFICATION

Support:	ABAX2
Alarm signaling:	Signal to control panel
Frequency band:	868 MHz ... 868.6 MHz
Radio communication range (at open area):	<ul style="list-style-type: none">• ≤ 2000 m @ ACU-220,• ≤ 1600 m @ ACU-280
Battery:	CR123A 3 V - 3.0 V (included)
Backup time:	~ 2 years
Environmental class EN 50130-5:	III
Main features:	<ul style="list-style-type: none">• Operation modes :<ul style="list-style-type: none">- Twilight Sensor- Light intensity measurement in the range of 2 lx and 250 lx- Option to select one of 16 detection thresholds- Immunity to short and accidental changes of light intensity- Temperature Sensor- Temperature measurement in the range: -30°C ... +70°C- Programmable temperature threshold• Bi-directional encrypted radio communication - AES• Transmission channel diversity - automatic selection of the one of 4 channels that will enable transmission without interference with other signals in the 868 MHz frequency band• Remote update of module software• Remote configuration• LED indication• The "ECO" option allows to extend the battery life up to four times (only in ABAX2)• battery diagnostics• High resistance to wind and weather• "Index of Protection" IP65

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation temp:	-30 °C ... 70 °C
Color:	White
Weight:	0.07 kg
Dimensions:	58 x 115 x 34 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

PRESENTATION

Internal view of the housing:



Mounting side view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------