

Code: WSS-218R

## AMPLIFIER **WSS-218R** 2x-18dB + K. ZWR TELMOR

Net: **21.98 EUR** Gross: **27.04 EUR**

The WSS-218R amplifier is designed to operation in CATV networks (due to return channel) and for individual RTV antenna installations. Device is supplying from built-in mains adapter with LED operation signaling. The WSS-218R amplifier is designed to use indoors.



### SPECIFICATION

Frequency range:	5 MHz ... 65 MHz 85 MHz ... 862 MHz
Number of inputs/outputs:	1 / 2
Input/output impedance:	75 Ω
Connectors type:	"F"
Gain :	18 dB
Gain adjustment:	5 dB ... 18 dB
S/N ratio:	4.5 dB
IMA3 60dB:	105 dBμV
Return loss:	> 10 dB
Return channel loss:	6 dB
Isolation between outputs:	> 20 dB
Power supply:	230 V AC
Power consumption:	4 W
Weight:	0.280 kg
Dimensions:	115 x 95 x 35 mm
Manufacturer / Brand:	TELMOR
Guarantee:	2 years

### PRESENTATION

Top view:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



In the kit:

