

Code: WSS-412R

AMPLIFIER **WSS-412R** 4x-12dB + K. ZWR TELMOR

Net: 112.51 PLN Gross: 138.39 PLN

The WSS-412R amplifier is designed to operation in CATV networks (due to return channel) and for individual RTV antenna installations. Device is supplying from built-in mains adapter with LED operation signaling. The WSS-412R amplifier is designed to use indoors.



SPECIFICATION

Frequency range:	5 MHz ... 65 MHz, 85 MHz ... 862 MHz (OUT 1) 85 MHz ... 862 MHz (OUT 2-4)
Number of inputs/outputs:	1 / 4
Input/output impedance:	75 Ω
Connectors type:	"F"
Gain :	12 dB
Gain adjustment:	0 dB ... 12 dB
S/N ratio:	4.5 dB
IMA3 60dB:	105 dBμV
Return loss:	> 10 dB
Return channel loss:	2 dB
Isolation between outputs:	> 20 dB
Power supply:	230 V AC
Power consumption:	4 W
Weight:	280 g
Dimensions:	115 x 95 x 35 mm
Manufacturer / Brand:	TELMOR
Guarantee:	2 years

PRESENTATION

Top view:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------