

Code: CA-6-P

## ALARM CONTROL PANEL **CA-6-P** SATEL

Net: **61.69 USD** Gross: **75.88 USD**

The CA-6-P alarm control panel allows to separate to two zones: completely separate alarm systems or zones with common inputs or internal zones.

Support via remote keypads equipped with LEDs.



### SPECIFICATION

Mainboard inputs:	6 pcs
Mainboard outputs:	5 pcs
Maximal number of supported inputs:	8 pcs
Maximal number of supported outputs:	5 pcs
Current-carrying capacity, low-current programmable outputs:	50 mA
Current-carrying capacity, high-current programmable outputs (+/-10%):	2.2 A - 2 pcs
Maximal load:	1.2 A
Users + admins:	12 + 1
Partitions:	—
Zones:	2
Expansion modules:	—
Events memory:	255
Timers:	4
Supported keypads:	max. 3
Supporting the wireless ABAX system via bus:	—
Keyboard included:	—
Enclosure included:	—
Protection class (Grade):	—
Power supply:	18 V AC / 100 mA
Operation temp:	-10 °C ... 55 °C
Permissible relative humidity:	93 %
Dimensions:	142 x 101 mm
Weight:	0.18 kg
Manufacturer / Brand:	SATEL

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

**PRESENTATION**

Control panel mainboard view:



In the kit:

