Code: INTEGRA-64-PLUS/IT

# ALARM CONTROL PANEL **INTEGRA-64-PLUS/IT** SATEL

Net: 247.26 EUR Gross: 247.26 EUR



Advanced alarm control unit providing alarm functions and optional implementation of home automation and access control systems.
Thanks to their full compliance with the EN50131 Grade 3 requirements, the INTEGRA Plus series control panels provide a perfect solution for implementing advanced security systems in facilities subject to considerable burglary risk, e.g. banks, jewelery shops or public utility buildings. A major advantage of the INTEGRA control units are their communication features combined with additional modules - GSM and TCP/IP.
System operation is possible with LCD keypads, partition keypads, keyfobs and proximity cards or remotely with PC or mobile phone. Flash firmware upgrade with a PC.

**SPECIFICATION**


| | |
|---|---|
| Mainboard inputs: | 16 pcs |
| Mainboard outputs: | 16 pcs |
| Maximal number of supported inputs: | 64 pcs |
| Maximal number of supported outputs: | 64 pcs |
| Current-carrying capacity, low-current programmable outputs: | 50 mA |
| Current-carrying capacity, high-current programmable outputs (+/-10%): | 3 A - 4 pcs |
| Maximal load: | 3.5 A |
| Users + admins: | 192 + 8 |
| Partitions: | 8 |
| Zones: | 32 |
| Expansion modules: | max. 64 |
| Events memory: | 5631 |
| Timers: | 64 |
| Supported keypads: | max. 8 pcs |
| Supporting the wireless ABAX system via bus: | ✔ |
| Keyboard included: | — |
| Enclosure included: | — |
| Protection class (Grade): | 3 |
| Main features: | • Access control and home automation functions<br>• Built-in advanced power adapter with extended diagnostics<br>• Control panel programming and firmware upgrade via mini USB socket |
| Power supply: | 20 V AC / 337 mA |
| Operation temp: | -10 °C ... 55 °C |
| Permissible relative humidity: | 93 % |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


| | |
|---|---|
| Dimensions: | 264  x 134 mm |
| Weight: | 0.28 kg |
| Supported languages: | Italian |
| Manufacturer / Brand: | SATEL |
| Guarantee: | 2 years |

**PRESENTATION**

Control panel mainboard:



In the kit:




**PACKAGE**

| | |
|---|---|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60