

Code: XDL12TTAM1

OUTDOOR PIR AND MICROWAVE DUAL DETECTOR XDL12TTAM1 PYRONIX

Net: 106.70 EUR Gross: 131.24 EUR



The XDL12TTAM1 detector are two dual-element passive infrared sensors with microwave unit for outdoor applications. It is designed to outdoor usage in most severe and extreme acclimate conditions that may also accommodate pets up to 24 kg.

High reliability is achieved by hardware combining technologies such as Tri-Digital Detection Signal Processing and Tri-Anti-Mask Technology, reducing practically false alarms alerts to zero.

SPECIFICATION

Application:	Outdoor
Sensor type:	2 x PIR detector + Microwave (MW)
Pyroelectric sensor:	Double x 2
Range:	12 m
Detection angle:	85 ° / 17 °
Sensitivity adjustment:	✓
Autodiagnostics:	✓
Alarm output:	NC / EOL-NC / 2EOL-NC / 3EOL-NC
Pet immunity:	≤ 24 kg
Prealarm feature:	—
Maximal outputs load:	60 V DC / 50 mA
Digital temperature compensation:	✓
Antimask feature:	✓
Microwave frequency band:	10.515 GHz, 10.525 GHz, 10.535 GHz, 10.579 GHz
Power supply:	9 ... 16 V DC
Maximal current consumption:	24 mA @ 13.8 V

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

LED indication:	<ul style="list-style-type: none"> • MW detector • PIR detector • Alarm signaling
Recommended installation height:	1.2 m
Target speed range:	0.25 ... 2.5 m/s
Main features:	<ul style="list-style-type: none"> • "Index of Protection" - IP55 • EN 50131-2-4, EN 50131-1 • Advanced digital algorithm of vegetation sway elimination (trees, bushes) • digital detection algorithm with temperature compensation for high immunity to false alarms and repeatability of parameters • Immunity to environmental changes • Creep zone control • Tamper detection - opening the enclosure, removing from mounting surface • Blocking function - detecting potential intruders behind the obstacles and prevents arming the system until the function is reset with a walk test
Operation temp:	-30 ... 70 °C
Protection class (Grade):	Grade 3
Color:	Light gray
Weight:	0.362 kg
Dimensions:	180 x 84 x 75 mm
Manufacturer / Brand:	PYRONIX
SAP Code:	361300882
Manufacturer's code:	XDL12TT-AM
Guarantee:	5 years

PRESENTATION


Front view:




Rear view:



Internal view of the housing:



Detector range:



A - horizontal
B - vertical
In the kit:

