

Code: 3-12V/2A/BL

## SWITCHING ADAPTER 3-12V/2A/BL USB

Net: 9.67 EUR Gross: 11.89 EUR

The multi-range power supply enables the selection of a specific value of the output voltage in the range of 3V ... 12V DC. Additionally, the power supply has a 5V/1.2A USB port. Adapter operation is indicated by LED placed on the casing box.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current. Please pay attention for proper cooling conditions of the power adaptor during work!

**Attention!** Before connecting, be sure to check the polarity.



### SPECIFICATION

Model identifier:	3-12V/2A/BL
Input voltage:	100 ... 240 V AC
AC input frequency:	50 / 60 Hz
Output voltage:	3.0 V, 4.5 V, 5.0 V, 6.0 V, 7.5 V, 9.0 V, 12.0 V DC
Output current:	max. 2.0 A @ DC , max. 1.2 A @ USB
Output power:	30.0 W
Adapter type:	Switching
Output voltage adjustment:	✓
Protections:	Overvoltage
Number of outputs:	1 pcs
Power connectors type:	<ul style="list-style-type: none"><li>• AC : 230 V CEE 7/16</li><li>• DC - Angular plug : Replaceable plug tips - 7 pcs (2.5/0.7mm, 3.0/1.0mm, 3.5/1.3mm, 4.0/1.7mm, 5.0/1.7mm, 5.5/2.1mm, 5.5/2.5mm)</li><li>The possibility of changing the polarity by inserting the plug appropriately</li><li>• USB-A : 5 V / 1.2 A</li></ul>
Housing type:	Casing with plug
Length of the cable:	1.2 m
Weight:	0.128 kg
Dimensions:	85 x 50 x 72 mm
Guarantee:	2 years

### PRESENTATION

Output voltage adjustment:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Port USB:



Connector:



The power adapter is equipped with 7 replaceable DC plugs:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

