
Code: PSDCSEP-04124

# SWITCHING ADAPTER **PSDCSEP-04124**

Net: 142.94 EUR Gross: 142.94 EUR

Power adapter is equipped with aesthetic, solidly made metal casing box. Power adapter output voltage is DC 12 ... 15V. It allows to connect up to 4 devices with separate adjustment and galvanic isolation of each channel. Maximal load for the one output is 1A, but you should remember the total load for all outputs must be lower than 4A. Each output is protected independently with glass or PTC polymer fuse (jumper selection).
Please pay attention for proper cooling conditions of the power adaptor during work!




**SPECIFICATION**


| | |
|---|---|
| Adapter type: | Switching |
| Output voltage: | 12 ... 15 V DC |
| Output voltage adjustment: | Separate adjustment for each channel - By potentiometer |
| Max. output current (total): | 4 A |
| Max. output current for single output: | 1 A |
| Outputs protection: | 4 x 1 A - Glass Fuse |
| LED indication: | ✔ |
| Main features: | 4 separate, galvanic isolated outputs |
| Protection: | • Short-circuit<br>• Overload<br>• Overvoltage<br>• Overvoltage |
| Input voltage: | 85 V ... 264 V AC |
| Power: | 48 W (max) |
| Number of outputs: | 4 |
| Connector type: | Cable terminals |
| Housing type: | Metal, wall-mounted |
| Key closed: | – |
| Weight: | 2.3 kg |
| Dimensions: | 220 x 210 x 80 mm |
| Manufacturer / Brand: | PULSAR |
| Guarantee: | 2 years |

**PRESENTATION**

Internal view of the housing:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Power adapter in closed casing:




Mounting side view:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Dimensions:




**PACKAGE**

| | |
|---|---|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60