Code: IEC-W/ZAC-TRI113/MSR

COMPRESSION PLUG IEC-W/ZAC-TRI113/MSR

Net: 0.49 EUR Gross: 0.49 EUR

The connector is equipped with a plastic bush, which during compression of the connector is tightly pressed against the sheath of the cable (by putting on cone brass case - the compression ring). The IEC-W/ZAC-TRI113/MSR professional compression connector fulfills all recommendations of SCTE (The Society of Cable Telecommunications Engineers) for this kind connectors. The features of the connector have been specially matched to the TRISET-113 cables. The dimensions are so matched that after compression connector is crimped on the cable sheath with a force so large that break the connector from the cable is impossible and so small that it does not damage the structure of the cable.



SPECIFICATION

Connector type:	IEC Straight plug
Attachment of connector elements:	Compression mounting
Shield fastening:	Compression mounting
Wire mounting:	Pressing
Application:	Coaxial cable
Cable diameter:	max. 8.0 mm
Impedance:	75 Ω
Material:	Brass (Nickel-platted)
Watertightness:	✓
Example of application:	Triset-Profi, Triset113, Triset-113PE, Triset-113HF
Main features:	Wide frequency range Watertightness of connector with cable connection Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric Very low loss in the whole operating band Perfect matching to the transmission line within the whole operating band Properly compressed connection is highly resistant to break Many patent-pending solutions To crimp use the crimping tool HT-5082R
Weight:	0.009 kg
Dimensions:	Ø 11.5 x 33 mm
Guarantee:	2 years

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-04-19