

Code: DRL-24V120W-1EN

SWITCHING ADAPTER **DRL-24V120W-1EN** LYTE II

Net: **35.02 EUR** Gross: **43.07 EUR**

Switching adapter installed on the TS35/7.5 or 15 DIN rail, resistant to high operation temperatures (up to 70°C).



SPECIFICATION

Adapter type:	Switching
Power voltage:	90 ... 264 V AC
Output voltage:	24 V DC
Output voltage adjustment:	21.6 ... 26.4 V DC
Maximal load:	5 A
Output power:	120 W
Number of outputs:	2 pcs
Efficiency:	88.5 %
Housing type:	DIN
Protections:	<ul style="list-style-type: none">• Short-circuit• Overload• Overvoltage• Temperature
Operation temp. / Relative humidity:	-40 °C ... 70 °C / 20 ... 95 %
Weight:	0.45 kg
Dimensions:	123.6 x 116.8 x 30 mm
Guarantee:	3 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front panel:



Connectors:





Mounting side view:



Rear panel (DIN rail installation):



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

