

Code: MDR-40-12

## SWITCHING ADAPTER **MDR-40-12**

Net: **31.38 EUR** Gross: **31.38 EUR**

Switching adapter installed on the TS35/7.5 or 15 DIN rail, resistant to high operation temperatures (up to 70°C).



### SPECIFICATION

|                                      |                                                                                                                     |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Adapter type:                        | Switching                                                                                                           |
| Power voltage:                       | 100 ... 240 V AC                                                                                                    |
| Output voltage:                      | 12 V DC                                                                                                             |
| Output voltage adjustment:           | 12 ... 15 V                                                                                                         |
| Voltage tolerance:                   | ± 1 %                                                                                                               |
| Maximal load:                        | 3.33 A                                                                                                              |
| Output power:                        | 40 W                                                                                                                |
| Number of outputs:                   | 2 pcs                                                                                                               |
| Efficiency:                          | 86 %                                                                                                                |
| Housing type:                        | DIN                                                                                                                 |
| MTBF (Mean Time Between Faults):     | 301700 hours                                                                                                        |
| Vibration resistance:                | IEC60068-2-6, 10 ... 500 Hz max. 2 G for 90 minutes                                                                 |
| Protections:                         | <ul style="list-style-type: none"><li>• Short-circuit</li><li>• Overvoltage</li><li>• Overload protection</li></ul> |
| Operation temp. / Relative humidity: | -20 °C ... 70 °C / < 90 %                                                                                           |
| Weight:                              | 0.26 kg                                                                                                             |
| Dimensions:                          | 40 x 90 x 100 mm                                                                                                    |
| Guarantee:                           | <b>3 years</b>                                                                                                      |

### PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Front panel:



Side view:



Rear panel (DIN rail installation):





DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60