

Code: 12V/10A/P

## SWITCHING ADAPTER 12V/10A/P

Net: 10.20 EUR Gross: 12.55 EUR

Power adapter with two pairs of output terminals.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current. Please pay attention for proper cooling conditions of the power adaptor during work! Inside Rack cabinets and at poor conditioning places we recommend to use together with adaptor the following elements: A19-W12 Rack Fan and FR-1 Fan Speed Control.

**Attention!** Both terminals of V- have a physical contact to each other, as well as the both terminals of V+



### SPECIFICATION

Adapter type:	Switching
Power voltage:	230 V AC
Output voltage:	12 V DC
Output voltage adjustment:	10.2 ... 15 V
Maximal load:	10 A
Output power:	120 W
Number of outputs:	2 pcs
Protections:	<ul style="list-style-type: none"><li>• Short-circuit</li><li>• Overload</li></ul>
Operation temp. / Relative humidity:	-10 °C ... 50 °C / 20 % ... 90 %
Weight:	0.452 kg
Dimensions:	200 x 98 x 42 mm
Guarantee:	2 years

### PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Adapter connectors:



L - Live wire (230V)  
N - Neutral wire  
GND - Grounding  
-V - DC "-" output  
+V - DC "+" output  
ADJ - Output voltage adjustment

## OUR OPINIONS



- The device may cause interference in some CCTV installations.