Code: ACAR-P7

POWER DISTRIBUTION UNIT **ACAR-P7** (5 + 2 OUTLETS)

Net: 15.33 EUR Gross: 15.33 EUR

The device reduces the risk of damage the computer, TV-set, radio receiver caused by surges in mains. The device is equipped with the two-way power switch with light indicator, which informs about the power voltage in outlets. Protection by fuse (automatic) on both current paths. Load nominal current 10A.




SPECIFICATION

Rated voltage:	230 V AC / 50 Hz
Total maximal current:	10 A
Maximal total load:	2300 W
Response time:	< 25 ns
Number of outlets:	5 grounded outlets 10A/250V 2 non-grounded outlets 2.5A/250V
Automatic delayed fuse:	10 A / 250 V
Leak current:	< 0.5 mA
Nominal voltage of surge suppressor:	250 V / 50 Hz
Protection level of surge suppressor:	≤ 1.3 kV (L/N)
Nominal stroke current:	2 kA (L/N) - (8/20μs)
Switch:	two-way, with light indication
Maximum stroke current:	6.5 kA (L/N) - (8/20μs)
Length of the cable:	1.45 m
Housing:	Plastic - non-flammable
Dimensions:	370 x 65 x 44 mm
Weight:	0.44 kg
Guarantee:	2 years

PRESENTATION

The extension cord has holders to arrange the cables:



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

OUR OPINIONS

- The automatic fuse allows to continuous work of the device without any breaks due to device overloads or short-circuits.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60