

Code: AXON-MINI/SAT

OVERVOLTAGE LIMITER **AXON-MINI/SAT** (1 + 2 OUTLETS) +SAT

Net: **5.96 EUR** Gross: **5.96 EUR**

The AXON-MINI/SAT overvoltage limiter ensures continuous protection against overvoltages of three devices and TV-SAT antenna signal line. It is equipped with one grounded power outlet, two flat non-grounded power outlets and two TV-SAT phone sockets. It is perfect solution to increase the functionality of the single surface power outlet and protect TV-SAT receiver against overvoltages of SAT antenna signal line.



SPECIFICATION

Rated voltage:	230 V AC / 50 Hz
Total maximal current:	10 A
Maximal total load:	2300 W
Response time:	< 25 ns
Number of outlets:	3 outlets, two-contact 10A/250V including 1 with ground contact
Leak current:	< 0.5 mA
Nominal voltage of surge suppressor:	250 V / 50 Hz
Protection level of surge suppressor:	≤ 1.3 kV (L/N)
Nominal stroke current:	2 kA (L/N) - (8/20 μ s)
Maximum stroke current:	6.5 kA (L/N) - (8/20 μ s)
Electric shock protection system:	Ground connectors (pins) connected with ground wire of AC mains
Housing:	Plastic - non-flammable
SAT LINE:	
SAT sockets type:	2 F type female sockets
SAT bandwidth:	950 ... 2150 MHz
Rise time of surge suppressor for SAT line:	< 25 ns
Nominal voltage of surge suppressor for SAT line:	95 V
Level of surge protection for SAT line:	≤ 0.6 kV
Nominal discharge current for SAT line:	2 kA (8/20 μ s) (wire/PE, shield/PE)
SAT line maximal stroke current:	5 kA (8/20 μ s) (wire/PE, shield/PE)

Dimensions:	131 x 55 x 75 mm
Weight:	0.13 kg
Guarantee:	2 years

PRESENTATION

In the kit:



Package:



OUR OPINIONS



- Integrated protection of power supply and SAT antenna signal line.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------