

Code: LZ-6

POWER SUPPLY DISTRIBUTOR LZ-6

Net: **6.91 USD** Gross: **8.50 USD**

The LZ-6 is a passive device and allows to distribute the power supply.

The housing of the LZ-6 has been prepared for mounting with screws to a wall or with a tie to a mast (tie, screws - not included).

An unquestionable advantage of employing the LZ-6 in monitoring systems powered from a central point is additional tamper protection. Without individual protection for each power line, an intruder can stop powering of the whole system just by shorting out the power line of the single camera.



SPECIFICATION

Number of power inputs:	2
Number of power outputs:	6
Maximal power voltage:	0 ... 24 V DC (typical 12V)
Maximal power supply current:	<ul style="list-style-type: none">• 6 A terminals• 4 A 5.5/2.1 socket
Protection type:	6 x 1 A 5/20mm delayed fuse
Power connectors type:	Input : socket 2.1/5.5 mm / Cable terminals Output : Cable terminals
Operation temp:	-50 °C ... 55 °C
Permissible relative humidity:	< 95 %
Dimensions:	120 x 91 x 37 mm
Weight:	0.099 kg
Manufacturer / Brand:	DELTA
Guarantee:	3 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

