

Code: LZ-5S/POL


POWER SUPPLY DISTRIBUTOR **LZ-5S/POL**

Net: **6.30 EUR** Gross: **7.75 EUR**

The LZ-5S/POL is a passive device and allows to distribute the power supply.

The housing of the LZ-5S/POL has been prepared for mounting with screws to a wall or with a tie to a mast (tie, screws - not included).

An unquestionable advantage of employing the LZ-5S/POL in monitoring systems powered from a central point is additional tamper protection. Without individual protection for each power line, an intruder can stop powering of the whole system just by shorting out the power line of the single camera.



SPECIFICATION

Number of power inputs:	2
Number of power outputs:	5
Maximal power voltage:	30 V DC (typical 12V)
Maximal power supply current:	<ul style="list-style-type: none">• 6 A terminals• 4 A 5.5/2.1 socket
Max. output current for single output:	750 mA
Protection type:	5 x 0.75 A Polymer fuse
Power connectors type:	Input : socket 2.1/5.5 mm / cable terminal (separable) Output : Cable terminals (separable)
Operation temp:	-50 °C ... 55 °C
Permissible relative humidity:	< 95 %
Dimensions:	120 x 91 x 37 mm
Weight:	0.097 kg
Manufacturer / Brand:	DELTA
Guarantee:	3 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Internal view, after remove the cover:



All cable terminals are separable, it allows to easy and quick connect or disconnect the power:



The distributor's housing can be easily installed to the walls using the screws and to the masts with a tie:

