

IP CAMERA TC-C38SS SPEC:I5/A/E/Y/M/H/2.7-13.5MM/V4.0 - 8 Mpx 2.7 - MOTOZOOM TIANDY

Net: **589.86 EUR** Gross: **589.86 EUR**

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 8 MPx.

The used motozoom lens with 2.7 ... 13.5 mm focal length allows to remote view angle adjustment. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



SPECIFICATION

Standard:	IP
Resolution:	3840 x 2160 - 8 Mpx , 3072 x 2048 - 6 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor:	1/2.7 " Progressive Scan CMOS
Lens:	2.7 ... 13.5 mm - Motozoom
View angle:	106 ° ... 31 °
Range of IR illumination:	50 m
Image compression method:	S+265 / H.265 / H.264
Main stream frame rate:	25 fps @ 8 Mpx
Interface:	10/100 Base-T (RJ-45)
Alarm inputs / outputs:	2 / 1
Audio:	• Audio input • Audio output • Microphone built-in • Audio transmission via network • Compliance with the AAC standard
WEB Server:	Built-in

Max. number of on-line users:	2
ONVIF:	✓
Memory card slot:	Micro SD card support up to 512GB
Mobile phones support:	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC:	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address:	192.168.1.2
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports:	3000, 3001
PC access port:	3000, 3001
Port ONVIF:	80
Intelligent image analysis:	• classification of people and vehicles • crossing the line (tripwire) • intrusion • double crossing the line • abandoned/missing object • parking detection • people counting • detection of people gathering • heat map • detection of loitering in a given area • running • protective helmet detection • detection of persons on duty • video tampering
Main features:	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Day/Night mode - configurable • Motion Detection • Privacy zones • Sharpness - sharper image outlines
Power supply:	• PoE (802.3af), • 12 V DC / 750 mA
Power consumption:	≤ 9 W
Housing:	Dome - Metal
Color:	White + Black
"Index of Protection":	IP66
IK rating:	—
Operation temp:	-35 °C ... 65 °C
Weight:	0.69 kg
Dimensions:	Ø 132 x 108 mm
Supported languages:	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, Portuguese, Russian, Thai, Turkish, Vietnamese, German, Ukrainian, Italian
Manufacturer / Brand:	TIANDY
Guarantee:	3 years



PRESENTATION

Internal view:



Memory card slot:



Side view:



Mounting side view:



In the kit:



PACKAGE

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

