

Code: POE-802.3AF

## STABILIZER 48V/12V **POE-802.3AF**

Net: **13.67 EUR** Gross: **16.81 EUR**



The POE-802.3AF allows to supply the devices with DC 12V.

### SPECIFICATION

Standards:	PoE (802.3af), PoE (802.3at)
Input socket:	RJ-45 (T568B, T568A)
Number of inputs:	1 x RJ-45 socket - PoE
Number of outputs:	1 x RJ-45 plug 1 x 2.1/5.5 mm plug on the cable
Input voltage:	44 - 57 V PoE
Output voltage:	12 V DC +/- 5%
Output current:	max. 1A / 12V DC @ 48 V PoE max. 0,8A / 12V DC @ 57 V PoE
Supported data rates:	<ul style="list-style-type: none"><li>• Ethernet - 10 Mbps Half Duplex</li><li>• Fast Ethernet - 100 Mbps Full Duplex</li></ul>
Maximal transmission range:	100 m (DATA)
LEDs application:	<ul style="list-style-type: none"><li>• Power supply PoE - Yellow</li><li>• NC - Green</li></ul>
Certificates:	CE, FCC Class B
Weight:	0.060 kg
Dimensions:	86 x 32 x 26 mm
Guarantee:	2 years

### PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Connectors:





See how you can power the camera in PoE standard:

