

Code: SPT-1G/1GP-30W-S

POE POWER ADAPTER **SPT-1G/1GP-30W-S** 30 W

Net: **23.14 EUR** Gross: **28.46 EUR**

Switching adapter, it is designed to powering IP devices using PoE technology.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current. Please pay attention for proper cooling conditions of the power adaptor during work!



SPECIFICATION

Standards:	<ul style="list-style-type: none">• IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x• PoE IEEE 802.3af, IEEE 802.3at
Input voltage:	100 V ... 240 V AC
Output voltage:	52 V DC
Number of inputs:	1
Connector:	2 x RJ-45 socket
Maximal output current:	580 mA
LED indicators:	Power, PoE
Output power:	30 W
Protections:	Overload
Supported data rates:	10 / 100 / 1000 Mbps - Gigabit Ethernet
Main features:	MDI/MDI-X auto detection feature - auto detecting the data transmission mode
Housing:	Plastic
Operation temp. / Relative humidity:	-20 ... 50 °C / 10 ... 90 %
Weight:	0.18 kg
Dimensions:	166 x 55 x 40 mm
Guarantee:	2 years

PRESENTATION

Connectors:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:

