

Code: DL2-100-24-U

SWITCHING ADAPTER **DL2-100-24-U**

Net: **33.85 EUR** Gross: **33.85 EUR**

Switching adapter installed on the TS35/7.5 or 15 DIN rail, resistant to high operation temperatures (up to 70°C).



SPECIFICATION

Adapter type:	Switching
Power voltage:	• 85 ... 264 V AC • 120 ... 370 V DC
Output voltage:	24 V DC
Output voltage adjustment:	21.6 ... 29 V DC
Maximal load:	4.2 A
Output power:	100.8 W
Number of outputs:	2 pcs
Efficiency:	90 %
Housing type:	DIN
Protections:	• Short-circuit • Overload • Overvoltage
Operation temp. / Relative humidity:	-40 °C ... 70 °C / 10 ... 95 %
Weight:	0.25 kg
Dimensions:	92.7 x 70 x 58 mm
Guarantee:	3 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Adapter connectors:



Top view:




Rear panel (DIN rail installation):





Dimensions:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------