

Code: DRS-24V30W-1AZ

SWITCHING ADAPTER **DRS-24V30W-1AZ**

Net: **21.50 EUR** Gross: **26.45 EUR**

Switching adapter installed on the TS35/7.5 or 15 DIN rail, resistant to high operation temperatures (up to 70°C).



SPECIFICATION

Adapter type:	Switching
Power voltage:	85 ... 264 V AC
Output voltage:	24 V DC
Output voltage adjustment:	21.6 ... 26.4 V
Voltage tolerance:	< 1 %
Maximal load:	1.25 A
Output power:	30 W
Number of outputs:	1 pcs
Efficiency:	88 %
Housing type:	DIN
MTBF (Mean Time Between Faults):	700000 hours
Vibration resistance:	IEC60068-2-6, 10 ... 150 Hz max. 2 G for 60 minutes
Protections:	<ul style="list-style-type: none">• Short-circuit• Overvoltage• Overload protection• Temperature
Operation temp. / Relative humidity:	-20 °C ... 70 °C / 5 % ... 95 %
Weight:	0.1 kg
Dimensions:	21 x 89.5 x 75 mm
Guarantee:	5 years

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

PRESENTATION


Front panel:



Rear panel (DIN rail installation):



Side view:



Dimensions:

