

Code: CD-65A4

## CARBON MONOXIDE (CO) DETECTOR **CD-65A4** EURA

Net: **19.80 EUR** Gross: **24.35 EUR**

The CD-65A4 microprocessor-based digital gas detectors are characterized by reliability and low current consumption. A digital temperature compensation feature allows to operate within a wide temperature range.

Gas concentration above the threshold level triggers visual and audible alarm signals. Device should be mounted at a height of about 0.7 ... 1.5 m above the floor.



### SPECIFICATION

Detection:	Carbon Monoxide (CO)
Alarm signaling:	<ul style="list-style-type: none"><li>• Buzzer</li><li>• Blinking LED</li></ul>
Gas concentration to trigger alarm:	300 ppm for max. 3 mins
Battery power supply:	3 x battery LR6 (AA) (included) Current consumption < 90 µA - Standby
Main features:	<ul style="list-style-type: none"><li>• Low battery level alarm</li><li>• Alarm siren 85 dB/m</li><li>• Test mode</li><li>• Detection max. 25 m<sup>2</sup></li><li>• LCD display</li><li>• Thermometer built-in</li><li>• Displays the concentration of the CO gas in the air in range of 25 ... 550 ppm</li></ul>
Operation temp:	0 °C ... 40 °C
Weight:	0.226 kg
Dimensions:	120 x 90 x 40 mm
Manufacturer / Brand:	EURA
Guarantee:	2 years

### PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Front panel:



Internal view:



Mounting side view:



In the kit:

