

Code: DG-1-CO

## CARBON MONOXIDE (CO) DETECTOR **DG-1-CO** SATEL

Net: **43.25 USD** Gross: **53.20 USD**

The DG-1-CO microprocessor-based digital gas detectors are characterized by reliability and low current consumption. A digital temperature compensation feature allows to operate within a wide temperature range. Gas concentration above the threshold level triggers visual and audible alarm signals. The detectors are intended to be used as part of a security system. Device should be mounted at a height of about 1.5 m above the floor.



### SPECIFICATION

Detection:	Carbon Monoxide (CO)
Alarm signaling:	<ul style="list-style-type: none"><li>• Buzzer</li><li>• Blinking LED</li><li>• Signal to control panel</li></ul>
Gas concentration to trigger alarm:	<ul style="list-style-type: none"><li>• 50 ppm for 75 minutes</li><li>• 100 ppm for 25 minutes</li><li>• 300 ppm for 1 minute</li></ul>
Maximum permissible load:	16 V DC / 40 mA
Power supply:	9 ... 20 mA / 12 V DC
Operation temp:	-30 °C ... 55 °C
Weight:	0.050 kg
Dimensions:	Ø 97 x 36 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

### PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

View after remove the cover:



Mounting side view + additional elements included in the kit:



Package:





DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60