

Code: DS-PDMCK-EG2-WE

WIRELESS MAGNETIC CONTACT WITH SHOCK DETECTOR AX PRO **DS-PDMCK-EG2-WE** Hikvision

Net: **38.65 EUR** Gross: **47.54 EUR**

The DS-PDMCK-EG2-WE wireless detector is intended for installation in locations where a shock detector is required or a combination of this detector with a magnetic contact, such as walls, ceilings, door and window frames.

The DS-PDMCK-EG2-WE supports the other devices compatible with wireless HIKVISION AX PRO system.



SPECIFICATION

Support:	HIKVISION AX PRO
Detection:	<ul style="list-style-type: none">• Opening the door or window,• Vibrations, Shocks, tilt < 25 °
Break distance:	~ 43 mm
Alarm signaling:	Signal to control panel
Frequency range:	868 MHz - Tri-X Wireless
Radio communication range (at open area):	max. 1600 m
Alarm inputs:	2 pcs NO/NC
Power supply:	1 x battery CR123A 3 V (included)
Backup time:	~ 3 years
Current consumption:	max. 70 mA
Main features:	<ul style="list-style-type: none">• Tamper protections• Signal indicator• LED indication• Digital detector• Transmission encoding - 128-bit AES encryption• Bidirectional communication• Frequency hopping against jamming for reliable transmission• Input : NO/NC

Complies with norms:	EN50131-1:2006+A1:2009, EN50131-1:2006+A2:2017 EN50131-2-8:2016 EN50131-2-6:2008 EN 50131-5-3:2017
Environment class:	II
Operation temp:	-10 °C ... 55 °C
Color:	White
Weight:	<ul style="list-style-type: none"> • 0.046 kg - Transmitter • 0.012 kg - Magnet
Dimensions:	<ul style="list-style-type: none"> • 22 x 103 x 23 mm - Transmitter • 13 x 34 x 11 mm - Magnet
Country of origin:	China
SAP Code:	314300097
Manufacturer / Brand:	Hikvision
Guarantee:	2 years

PRESENTATION

Front view:



Internal view of the housing:



Mounting side view:



In the kit:

