

Code: DS-PDMCX-E-WE

WIRELESS EXTERNAL MAGNETIC CONTACT AX PRO **DS-PDMCX-E-WE**

Hikvision

Net: **62.77 EUR** Gross: **62.77 EUR**



The DS-PDMCX-E-WE wireless detector (magnetic contact) is designed for outdoor usage. Robust plastic housing, UV stable. The product meets the IP66 tightness class.

The DS-PDMCX-E-WE supports the other devices compatible with wireless HIKVISION AX PRO system.

SPECIFICATION

Support:	HIKVISION AX PRO
Detection:	Gate opening, Opening the door
Break distance:	~ 76 mm
Alarm signaling:	<ul style="list-style-type: none">• LED indicator : Color - blue,• Signal to control panel
Frequency range:	868 MHz - Tri-X Wireless
Radio communication range (at open area):	max. 1600 m
Alarm inputs:	NO/NC
Power supply:	1 x battery CR123A 3 V (included)
Backup time:	~ 5 years
Current consumption:	max. 48 mA
Main features:	<ul style="list-style-type: none">• Tamper detection - opening the enclosure, removing from mounting surface• Signal indicator• Digital detector• Transmission encoding - 128-bit AES encryption• Bidirectional communication• Frequency hopping against jamming for reliable transmission• Remote management• UV radiation resistance• "Index of Protection" : IP66
Operation temp:	-20 °C ... 60 °C



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Color:	White
Weight:	<ul style="list-style-type: none">• 0.156 kg - Transmitter• 0.096 kg - Magnet
Dimensions:	<ul style="list-style-type: none">• 41 x 146 x 41 mm - Transmitter• 31 x 146 x 41 mm - Magnet
Country of origin:	China
SAP Code:	314300151
Manufacturer / Brand:	Hikvision
Guarantee:	2 years

PRESENTATION

Front view:



Internal view of the housing:





Mounting side view:



In the kit:



PACKAGE

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

