

Code: ST-35IPC

IP, PAL VIDEO TESTER ST-35IPCNet: **179.38 EUR** Gross: **179.38 EUR**

Multi-functional tester of IP cameras, analog cameras, Speed Dome (PTZ) cameras has implemented many additional functions, necessary during initialization of the CCTV installation system. Due to ONViF protocol support the tester can be connected to the IP cameras using the applications running under Android, iOS systems.

Attention! The battery is disconnected from the device's motherboard at the factory. Before starting the device, open the battery compartment, and then connect it to the motherboard.

**SPECIFICATION**

Video standard:	• AHD - 5 Mpx, • HD-CVI - 4 Mpx, • HD-TVI - 5 Mpx, • TCP/IP - 8.3 Mpx, • CVBS - PAL / NTSC
Display:	3.5 " LCD, 320 x 240
Video input:	1 x AHD / HD-CVI / HD-TVI / CVBS - BNC socket
Video output:	—
Video signal level meter:	—
Video signal generator:	—
Serial ports:	RS-485
Protocols:	Pelco-P, Pelco-D, YAAN, YAAN-O, YAAN-1, SAMSUNG, PANASONIC, Lilin-FAST, Lilin-MLP2, MOLYNX, MINKING A01, Fastrax, CBC, LC-NEW, WV-CS850, SONY-EVI, LG-MULTIX, DAT-SD, VICON, Vcltp, DH-YTC 06, Santachi, Bosch OSRD, TeleEye DM2, HD 600, Hikvision, KALATEL ASC, AD 168(M-B), SAMSUNG SPD, Siemens, MINKING B01, ALEC
Baud rates:	150, 300, 600, 1200, 2400, 4800, 9600, 19200, 38400, 115200 b/s
RS-485 line:	Data analysis from control device (the commands are displayed in hexadecimal)
Network interface:	1 x RJ-45
Wi-Fi module:	✓
Wi-Fi standard:	• IEEE 802.11b, • IEEE 802.11g, • IEEE 802.11n
Network protocols:	TCP/IP, HTTP, FTP, RTSP
ONVIF:	✓
LAN (twisted-pair) or telephone cables testing:	• PING - test the link using ICMP packets • Data Flow Control Ethernet

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Identification the wire in the group of wires:	—
Memory:	External: microSD cards socket (card is not included)
Audio test:	Preamplifier and speaker built-in (JACK 3.5 mm socket)
Digital multimeter:	—
Optical power measurement:	—
TDR reflectometer:	—
Operation as power source:	12 V DC / 1 A
Power supply:	5 V DC / 1.5 A - mini USB
Battery:	3.7 V / 3000 mAh
Estimated battery operation time:	8 h
Operation:	OSD
Main features:	• Graphical menu - touch control and by using the buttons, • Support for IP cameras and network devices, • Support for DHCP automatic address configuration, • LAN connections monitoring, • IP addresses scanner, • Searching and view of IP cameras compatible with Onvif, • Detection of the connected port in switch, • Motor units and PTZ (Speed Dome) cameras control, • IP cameras view from embedded applications : iVMS-4500 HD, BSR MPlayer, Easy Mobile, MEye, NetVideo, PT-VSS, Wision, TSee, iCamPlayer, Safire Control Center • Embedded Internet browser, • Video recording to micro SD card with playback possibility • Video recording format : .h264 • Pictures recording format : .jpg • Calculator
Supported languages:	English, Chinese, French, Spanish, Korean, Polish, Russian, Italian
Operation temp:	-10 ... 50 °C
Weight:	0.240 kg
Dimensions:	120 x 80 x 32 mm
Guarantee:	2 years

PRESENTATION

Front panel:



Device connectors:



Memory card slot:







Battery:






Rear view:



OSD menu:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



Device is secured by handy case:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

