Code: CS-H7-50H

MULTI-FUNCTIONAL CCTV TESTER **CS-H7-50H**

Net: 325.19 EUR Gross: 325.19 EUR

Multi-functional tester of AHD, HD-CVI, HD-TVI, IP cameras, analog cameras, Speed Dome (PTZ) cameras has implemented many additional functions, necessary during initialization of the CCTV installation system.



SPECIFICATION

Video standard:	• AHD - 8 Mpx, • HD-CVI - 8 Mpx, • HD-TVI - 8 Mpx, • TCP/IP - 4K, • CVBS - PAL / NTSC
Display:	5 " - capacitive touch screen - 1920 x 1080 px
Video input:	• 1 pcs AHD / HD-CVI / HD-TVI / CVBS - BNC socket, • 1 pcs HDMI • 1 pcs VGA
Video output:	–
Port LAN:	2 pcs - PoE cameras and switches support
Audio input:	1 pcs Mini Jack
Audio output:	–
Video signal level meter:	–
Video signal generator:	–
Serial ports:	RS-485
Protocols:	Support for over 30 RS485 protocols Pelco-D, Pelco-P, YAAN, YAAN-O, YAAN-1, SAMSUNG, PANASONIC, Lilin-FAST, Lilin-MLP2, MOLYNX, MINKING A01, Fastrax, CBC, LC-NEW, WV-CS850, SONY-EVI, LG-MULTIX, DAT-SD, VICON, Vcltp, DH-YTC 06, Santachi, Bosch OSRD, TeleEye DM2, HD 600, Hikvision, KALATEL ASC, AD 168(M-B), SAMSUNG SPD, Siemens, MINKING B01, ALEC
Baud rates:	150, 300, 600, 1200, 2400, 4800, 9600, 19200, 38400, 115200 b/s
LAN (twisted-pair) or telephone cables testing:	UTP cables or phone lines connecting test with RJ-45 connectors
RS-485, RS-232 lines test:	Data analysis from control device (the commands are displayed in hexadecimal)
Wi-Fi module:	2.4 GHz
Identification the wire in the group of wires:	–
Audio test:	✔

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Digital multimeter:	–
Optical power measurement:	–
VLS (VFL) - Visual Fault Locator of fiber cable:	–
TDR reflectometer:	Detecting and locating a cable break (UTP only)
Operation as power source:	• 12 V DC / 3 A • 48 V (PoE, LAN), 25.5 W
Battery power supply:	• Li-Ion battery 7.4 V / 3350 mAh • 12 V DC / 2 A (power adapter included)
Estimated battery operation time:	max. 6 hours
Operation:	Graphic menu - touch control
Main features:	• AHD cameras test • HD-CVI cameras test • HD-TVI cameras test • PAL/NTSC cameras test • IP cameras test - Supported image compression methods : H.265, H.264, MJPEG • Format support : 5 Mpx, 16 : 9 HD-CVI, DAHUA • Searching and view of IP cameras compatible with Onvif • Virtual IPC • Bitrate Calculator • DH test tool • Hik test tool • UNV Test Tool • HuaWei Tool • Motor units and PTZ (Speed Dome) cameras control • IP cameras view from embedded applications - iVMS-4500 HD, EZView, gDMSS HD Lite, XMEye, MEye, Fseye • Embedded Internet browser - Google Chrome • LAN connections monitoring • IP addresses scanner • PING - test the link using ICMP packets • Detection of the connected port in switch • LAN (twisted-pair) cables testing • PoE cameras and switches support • PoE power meter • DC 12V / 48V power source • Data monitor - serial port data analysis RS-485 • Audio test • Hotspot - Wi-Fi • Video recording to micro SD card with playback possibility (not included) • Playback the records • Calculator • Flashlight built-in • Android 10
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	30 % ... 90 %
Weight:	0.42 kg
Dimensions:	184 x 110 x 40 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Spanish, German, Portuguese, Russian, Turkish, Italian
Guarantee:	2 years

PRESENTATION

Front panel (main menu options visible):



Connectors:





Rear view:

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60





Battery view after open the cover:




Main menu:






Brak sygnału wideo na wejściu !


Network & Cable Tester









Kamery IP



Kamery IP



PoE
Wyjście zasilania DC:WYŁ




IP Discovery
Finding Cameras...



ONVIF


NON ONVIF


HIK test tool


DH test tool


HK Tool


















DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


















DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60







In the kit:



The tester with accessories housed in a handy bag:



OUR OPINIONS

- Everything you need to work is the compact, small, universal device.
- Perfect to build and create the CCTV system.
- Supports HD-CVI standard in 5 Mpx resolution and 16:9 aspect ratio.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg