

Code: SD22204I-GC

HD-CVI, PAL SPEED DOME CAMERA OUTDOOR **SD22204I-GC** - 1080p 2.7 ... 11 mm DAHUA

Net: **249.19 EUR** Gross: **249.19 EUR**

Megapixel camera with 1/2.7" CMOS sensor and HD-CVI (High Definition Composite Video Interface). The HD-CVI interface allows to transmission of analog, composite video signal via coaxial cable. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image. Camera is according to IP66 Index of Protection norm.



SPECIFICATION


Standard:	HD-CVI, PAL
Sensor:	1/2.7 " Progressive Scan Exmor CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H
Range of IR illumination:	—
Lens:	2.7 ... 11 mm
View angle:	112.5 ° ... 30 °
Optical zoom:	x 4
Digital zoom:	x 16
Rotation speed depending on ZOOM level:	✓
Horizontal rotation range:	355 °, Rotation of the head is limited by stops
Vertical rotation range:	0 ° ... 90 °
Rotation speed (manual control):	0.1 °/s ... 100 °/s (horizontal) , 0.1 °/s ... 60 °/s (vertical)
Preset rotation speed:	100 °/s (horizontal) , 60 °/s (vertical)
PTZ control:	Via interface RS-485 The ability to control via coaxial cable from recorder DAHUA, BCS, RAPID
Protocols:	Pelco-D, Pelco-P, DH-SD (auto detection)
S/N ratio:	> 55 dB

Video output:	HD-CVI / PAL, 1 Vpp 75 Ω
Audio:	—
Number of presets:	300
Route settings:	8
Horizontal scan:	✓
Park action:	Call the set function (tour, scan, etc.) after specified dwell time
Alarm inputs / outputs:	—
Main features:	• ICR - Movable InfraRed filter • 2D-DNR / 3D-DNR - Digital Noise Reduction • WDR - 120 dB - Wide Dynamic Range • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • 24 Configurable Privacy Zones
OSD menu:	✓
"Index of Protection":	IP66
Vandal-proof:	IK10
Power supply:	12 V DC / 1500 mA
Housing:	Speed Dome, Metal
Color:	White
Operation temp:	-30 °C ... 60 °C
Weight:	0.51 kg (with bracket)
Dimensions:	Ø 122 x 89 mm
Supported languages:	English, Polish
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

View after remove the cover:





Mounting dimensions:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with external IR illuminator on:



Camera image at direct strong light opposite to camera:



Camera image at night conditions, at different illumination values show below:

1 LUX:



0.1 LUX:



0.01 LUX:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

