

Code: DS-PWA64-KIT-WE

## ALARM KIT AX PRO **DS-PWA64-KIT-WE** Hikvision

Net: **296.44 EUR** Gross: **364.62 EUR**

The AX PRO DS-PWA64-KIT-WE alarm kit is ideal solution for those looking for a simple and reliable system with enhanced communication functions.

The kit includes: the "DS-PWA64-L-WE" Wireless Alarm Control Panel, the "DS-PDP15P-EG2-WE" Wireless PIR Detector, the "DS-PDMC-EG2-WE" Wireless Magnet Detector and the "DS-PKF1-WE" Wireless Remote Controller.



### SPECIFICATION

Number of supported wireless devices:	max. 64 pcs
Number of supported PIR Cameras:	max. 48 pcs (not included)
Partitions:	1 pcs
PIR detectors included:	1 pcs, Wireless
Magnetic contact included:	1 pcs, Wireless
The RFID cards/keyfobs support:	max. 32 pcs (not included)
Enclosure included:	✓
Keyboard included:	—
Timers:	✓
Number of supported readers:	max. 8 pcs (not included)
Number of supported wireless sirens:	max. 4 pcs (not included)
Number of supported remote control keyfobs:	max. 32 pcs In the kit : 1 pcs
Users + admins:	32 (30 + 1 + 1)
Expander included :	—
Wireless:	868 MHz
Operating range in open area:	≤ 2000 m
Built-in modules:	<ul style="list-style-type: none"><li>• Wi-Fi Module IEEE 802.11 b/g/n 2.4 GHz,</li><li>• LAN 10 / 100 Mbps,</li><li>• GPRS - It supports push messages, SMS text notifications, and audio notifications via the phone</li><li>• SIM socket</li></ul>
Access from PC:	iVMS-4200 application
Mobile phones support:	✓

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Main features:	<ul style="list-style-type: none"> <li>• Bidirectional communication - AES 128-bit data encryption</li> <li>• Support for video events via a mobile client and email</li> <li>• Configuration via the www client, mobile client or software</li> <li>• Compliance with the SIA-Contact ID protocol</li> <li>• Compliance with the Tri-X/Cam-X protocol</li> <li>• LED indication</li> </ul>
Protection class (Grade):	EN50131 Security Grade 2
Housing:	Plastic
Internal backup battery:	Li-Ion battery 4520 mAh, Battery backup - 12 h
Power supply:	100 ... 240 V AC (cable included)
Operation temp:	-10 °C ... 55 °C
Weight:	0.55 kg
Dimensions:	170 x 170 x 39 mm
Supported languages:	English

#### MAGNETIC CONTACT:

Detection:	Opening the door or window
Alarm signaling:	Signal to control panel
Frequency range:	868 MHz
Radio communication range (at open area):	max. 1600 m
Alarm inputs:	NO, NC
Protection class (Grade):	EN50131 Security Grade 2
Environment class:	Grade 2
Power supply:	1 x 3 V CR123A - included
Backup time:	~ 5 years
Operation temp:	-10 °C ... 55 °C
Weight:	0.06 kg
Dimensions:	<ul style="list-style-type: none"> <li>• 103 x 23 x 23 mm - Transmitter</li> <li>• 37 x 14 x 11 mm - magnet</li> </ul>

#### PIR DETECTOR:

Application:	Indoor
Frequency range:	868 MHz
Radio communication range (at open area):	max. 1600 m
Sensor type:	Passive Infra Red (PIR)
Detection range / Detection angle:	15 m / 85.9 °
Sensitivity adjustment:	Automatic
Pet immunity:	≤ 30 kg
Digital temperature compensation:	✓
Alarm output:	Wireless
Target speed range:	0.3 ... 2 m/s
Protection class (Grade):	EN50131 Security Grade 2
Power supply:	1 x 3 V CR123A - included
Battery lifetime:	~ 5 years
Operation temp:	-10 °C ... 55 °C



Weight:	0.12 kg
Dimensions:	66 x 103 x 49 mm
<b>REMOTE CONTROLLER:</b>	
Standard:	868 MHz
Radio communication range (at open area):	max. 900 m
In the kit:	1 pcs
Control keys:	4
LED indication:	✓
Power supply:	1 x 3 V CR2032 - included
Battery lifetime:	~ 3 years
Operation temp:	-10 °C ... 55 °C
Weight:	0.02 kg
Dimensions:	63 x 35 x 11 mm
<b>General information:</b>	
Manufacturer / Brand:	Hikvision
SAP Code:	302401696
Guarantee:	2 years

## PRESENTATION

Wireless Control Panel:



Bottom view (after remove the cover):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connectors:



Wireless detector:





Reed switch:



Remote controller:



In the kit:

