

Code: DS-PWA96-KIT-WE

ALARM KIT AX PRO **DS-PWA96-KIT-WE** Hikvision

Net: **509.39 EUR** Gross: **509.39 EUR**

The AX PRO DS-PWA96-KIT-WE alarm kit is ideal solution for those looking for a simple and reliable system with enhanced communication functions.

The kit includes: the "DS-PWA96-M-WE" Wireless Alarm Control Panel, the "DS-PDP15P-EG2-WE" Wireless PIR Detector, the "DS-PDMC-EG2-WE" Wireless Magnet Detector, the "DS-PKF1-WE" Wireless Remote Controller and the "MF-Y3" Key Fobs - 3 pcs.



SPECIFICATION

Number of supported wireless devices:	max. 96 pcs
Number of supported PIR Camera Detectors:	max. 48 pcs (not included)
Zones:	32
PIR detectors included:	1 pcs, Wireless
Magnetic contact included:	1 pcs, Wireless
The RFID cards/keyfobs support:	max. 48 pcs In the kit : 3 pcs
Enclosure included:	✓
Keyboard included:	—
Timers:	2
Number of supported readers:	max. 8 pcs RFID proximity reader built-in : 1 pcs
Number of supported wireless sirens:	max. 6 pcs (not included)
Number of supported remote control keyfobs:	max. 48 pcs In the kit : 1 pcs
Users + admins:	48 (46 + 1 + 1)
Expander included :	—
Wireless:	868 MHz
Built-in modules:	• Wi-Fi module IEEE 802.11 b/g/n 2.4 GHz, • LAN 10 / 100 Mbps, • 3G/4G - It supports push messages, SMS text notifications, and audio notifications via the phone • 2 x SIM socket
Access from PC:	iVMS-4200 application
Mobile phones support:	✓

Main features:	• Bidirectional communication - AES-128 data encryption • Support for video events via a mobile client and email • Configuration via the www client, mobile client or software • Compliance with the SIA-Contact ID protocol • LED indication
Protection class (Grade):	EN50131 Security Grade 2
Housing:	Plastic
Internal backup battery:	Li-Ion battery 4520 mAh, Battery backup - 12 h
Power supply:	100 ... 240 V AC (cable included)
Operation temp:	-10 °C ... 55 °C
Weight:	0.56 kg
Dimensions:	170 x 170 x 39 mm
Supported languages:	English

MAGNETIC CONTACT:

Detection:	Opening the door or window
Alarm signaling:	Signal to control panel
Frequency range:	868 MHz
Radio communication range (at open area):	max. 1600 m
Alarm inputs:	NO, NC
Protection class (Grade):	EN50131 Security Grade 2
Environment class:	Grade 2
Power supply:	1 x 3 V CR123A - included
Backup time:	~ 5 years
Operation temp:	-10 °C ... 55 °C
Weight:	0.06 kg
Dimensions:	• 103 x 23 x 23 mm - Transmitter • 37 x 14 x 11 mm - magnet

PIR DETECTOR:

Application:	Indoor
Frequency range:	868 MHz
Radio communication range (at open area):	max. 1600 m
Sensor type:	Passive Infra Red (PIR)
Detection range / Detection angle:	15 m / 85.9 °
Sensitivity adjustment:	Automatic
Pet immunity:	≤ 30 kg
Digital temperature compensation:	✓
Alarm output:	Wireless
Target speed range:	0.3 ... 2 m/s
Protection class (Grade):	EN50131 Security Grade 2
Power supply:	1 x 3 V CR123A - included
Battery lifetime:	~ 5 years
Operation temp:	-10 °C ... 55 °C
Weight:	0.12 kg



Dimensions:	66 x 103 x 49 mm
-------------	------------------

REMOTE CONTROL:

Standard:	868 MHz
Radio communication range (at open area):	max. 900 m
In the kit:	1 pcs
Control keys:	4
LED indication:	✓
Power supply:	1 x 3 V CR2032 - included
Battery lifetime:	~ 3 years
Operation temp:	-10 °C ... 55 °C
Weight:	0.016 kg
Dimensions:	63 x 35 x 11 mm

RFID PROXIMITY KEY-FOB:

Standard:	13.56 MHz S50
Operation range:	5 ... 10 cm
"Index of Protection":	IP67
In the kit:	3 pcs
Weight:	0.004 kg
Dimensions:	40 x 32 x 4 mm

General information:

Manufacturer / Brand:	Hikvision
SAP Code:	302401684
Guarantee:	2 years

PRESENTATION

Wireless Control Panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Bottom view (after remove the cover):



Connectors:





Wireless detector:





Reed switch:





Remote control:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------