

Code: MCT84M

PROXIMITY READER **MCT84M** ROGER

Net: **83.52 EUR** Gross: **102.73 EUR**



Indoor reader of proximity cards and key-fobs designed to work in the RACS 5 access control and building automation system. MIFARE 13.56 MHz standard.

SPECIFICATION

Support:	RACS 5 (Roger)
Cards support:	MIFARE 13.56 MHz, MIFARE Ultralight, MIFARE Classic
Reading distance of prox-keys:	max. 5 cm
Keyboard built-in:	✓
Autonomous operation:	—
Doorbell button:	✓
Tamper output:	✓
Communication:	RS-485
Main features:	<ul style="list-style-type: none">• Tamper protection (detection of removing from mounting surface and enclosure opening)• Keypad backlight buttons• LED indication• Beep signal• Reads card numbers: CSN, SSN, MSN• Support for normal and long card reading method• Configuration through RS-485 (RogerVDM)• Firmware upgrade via RS-485 (Roger VDM) port
Power supply:	10 ... 15 V DC
Average current consumption:	~ 50 mA
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	10 ... 95 % (non-condensing)
"Index of Protection":	IP41

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Weight:	0.1 kg
Dimensions:	130 x 45 x 22 mm
Manufacturer / Brand:	ROGER
Guarantee:	3 years

PRESENTATION

Front panel:



Rear view:



Internal view, after remove the cover:



In the kit:

