

Code: MCT88M-IO

## PROXIMITY READER **MCT88M-IO** ROGER

Net: **244.06 EUR** Gross: **300.19 EUR**

Indoor reader of proximity cards and key-fobs designed to work in the RACS 5 access control and building automation system. MIFARE 13.56 MHz standard.



### SPECIFICATION

Support:	RACS 5 (Roger)
Cards support:	MIFARE 13.56 MHz, MIFARE Ultralight, MIFARE Classic, MIFARE DESFire, MIFARE Plus, NFC
Reading distance of prox-keys:	max. 7 cm
Keyboard built-in:	✓
Autonomous operation:	—
Doorbell button:	✓
Tamper output:	✓
Communication:	RS-485
Main features:	<ul style="list-style-type: none"><li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li><li>• Built-in Bluetooth module allowing to identify the user via the mobile application</li><li>• Support for normal and long card reading method</li><li>• Alarm inputs : 3 pcs - NO, NC, EOL, 2EOL, 3EOL</li><li>• Alarm outputs : 1 pcs Relay output NO/NC 30 V DC / 1.5 A + 2 pcs OC</li><li>• Keypad backlight buttons</li><li>• LED indication</li><li>• Beep signal</li><li>• Reads card numbers: CSN, SSN, MSN</li><li>• Configuration through RS-485 (RogerVDM)</li><li>• Firmware upgrade via RS-485 (Roger VDM) port</li></ul>
Power supply:	10 ... 15 V DC
Average current consumption:	~ 110 mA
Operation temp:	5 °C ... 40 °C
Permissible relative humidity:	10 ... 95 % (non-condensing)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

"Index of Protection":	IP41
Weight:	0.23 kg
Dimensions:	156 x 85 x 22 mm
Manufacturer / Brand:	ROGER
Guarantee:	<b>3 years</b>

## PRESENTATION

Front panel:



Rear view:



Internal view, after remove the cover:



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------