

Code: SXTG-5HPACD-SA

## ACCESS POINT WITH ANTENNA **SXTG-5HPACD-SA** MIKROTIK

The SXTG-5HPACD-SA is an integrated solution for professional outdoor wireless networks. Thanks to a unique construction, device offers unparalleled performance in such a compact device.

The casing made of UV resistant plastic is resistant to even the most severe weather conditions. The device is compatible with MikroTik RouterOS platform.



|                            |  |
|----------------------------|--|
| Frequency range:           | 5745 MHz ... 5825 MHz  |
| Antenna type:              | 13 dBi Integrated, 2Tx 2Rx MIMO  |
| Standards:                 | IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n  |
| Baud rates:                | 866 Mbps   |
| LAN ports:                 | 1 x 10/100/1000 Mbps   |
| Vertical beam width (V):   | 90 °   |
| Horizontal beam width (H): | 90 °   |
| Operation modes:           | Access Point, Access Point WDS, Sector Access Point, Client, WDS client, Router or Bridge - 4 The level of license MikroTik RouterOS |
| Protections:               | Overvoltage protection   |
| Transmitter power:         | 30 dBm   |
| Memory:                    | 128 MB RAM, 128 MB NAND  |
| Processor:                 | QCA9882 720 MHz  |
| Port USB:                  | 2.0  |

|                       |   |
|-----------------------|---|
| Power supply PoE:     | ✓   |
| Power supply:         | <ul style="list-style-type: none"><li>• 15 V ... 60 V DC PoE (the set includes a power supply with 2.1/5.5mm connector and a compatible PoE power adapter)</li><li>• PoE (802.3af/at)</li></ul> |
| Power consumption:    | 12 W  |
| Operation temp:       | -30 °C ... 80 °C  |
| Weight:               | 0.292 kg  |
| Dimensions:           | Ø 140 x 66 mm   |
| Manufacturer / Brand: | MikroTik  |
| Guarantee:            | 2 years   |