

Code: DH-PFM881

ACCESS POINT **DH-PFM881** DAHUA



The DH-PFM881 is an integrated solution for professional outdoor wireless networks. Thanks to a unique construction, device offers unparalleled performance in such a compact device.
The casing made of UV resistant plastic is resistant to even the most severe weather conditions.

Frequency range:	5470 MHz ... 5825 MHz
Antenna type:	15 dBi Integrated, 2Tx 2Rx MIMO
Standards:	802.11 a/n
Baud rates:	max. 300 Mbps
Wireless transmission range:	max. 5 km
Max. power consumption:	8 W
Ethernet interface:	2 x 10/100 Mbps BASE-TX (Cat. 5, RJ-45)
Vertical beam width (V):	15 °
Horizontal beam width (H):	40 °
Operation mode:	Client, WDS client, Access Point, Access Point WDS, Repeater
Protections:	15kV surge protection of radio line
Transmitter power:	23 dBm
Receiver sensitivity:	<ul style="list-style-type: none"> • -74 dBm @ 65 Mbps • -96 dBm @ 1 Mbps



DATA SHEET

Processor:	Atheros AR7240, 400 MHz
Port USB:	—
Power supply PoE:	✓
Power supply:	24 V / 0.5 A PoE (power adapter included)
Operation temp. / Relative humidity:	-30 °C ... 70 °C / 5 % ... 95 %
Weight:	0.3 kg
Dimensions:	270 x 83 x 50 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

