

Code: GRAFIX-15V3W-21

## AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA **GRAFIX-15V3W-21** - 720p 2.8 ... 12 mm

Megapixel camera with 1/3" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 720p resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

Setting the camera in PAL mode allows to obtain an image in 960H resolution. The appropriate signal format selection is done by tilting the joystick in the desired direction while switching voltage.



Standard:	AHD, HD-CVI, HD-TVI, PAL
Sensor:	1/3 " HDIS CMOS
Digital Image Processor:	DI3010
Matrix size:	1.3 Mpx
Resolution:	1280 x 720 - 720p, AHD-H, HD-CVI, HD-TVI , 960 x 576 - 960H, PAL
Range of IR illumination:	30 m
IR illuminator power adjustment:	Automatic
Lens:	2.8 ... 12 mm, 3 Mpx
View angle:	<ul style="list-style-type: none"> <li>• 81 ° ... 23 ° (manufacturer data)</li> <li>• 86 ° ... 31 ° (our tests result)</li> </ul>
S/N ratio:	> 50 dB
Video output:	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch



# DATA SHEET

Main features:	<ul style="list-style-type: none"><li>• The ability to control via coaxial cable from recorder</li><li>• ICR - Movable InfraRed filter</li><li>• AGC - Automatic Gain Control</li><li>• Sharpness - sharper image outlines</li><li>• Auto White Balance</li></ul>
OSD menu:	✓
Vandal-proof:	✓
"Index of Protection":	IP66
Power supply:	12 V DC / 390 mA
Power consumption:	4.7 W
Housing:	Dome - Metal
Color:	White
Operation temp:	-20 °C ... 50 °C
Weight:	0.52 kg
Dimensions:	Ø 116 x 89 mm
Supported languages:	English, Chinese
Guarantee:	2 years