

Code: DH-HAC-HDW1200RP-036

AHD, HD-CVI, HD-TVI, PAL CAMERA **DH-HAC-HDW1200RP-036** 0B - 1080p 3.6 mm DAHUA



Attention! The camera default setting is HD-CVI standard. To change the camera standard you need use the PFM820 controller, available separately.

Megapixel camera with 1/2.7" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

Standard:	AHD / HD-CVI / HD-TVI / PAL
Matrix size:	2.0 Mpx
Sensor:	1/2.7 " CMOS
Resolution:	1920 x 1080 - 1080p , 1280 x 720 - 720p
Range of IR illumination:	20 m
IR illuminator power adjustment:	Automatic
Lens:	3.6 mm, F2.0
View angle:	<ul style="list-style-type: none"> • 90 ° (manufacturer data) • 87 ° (our tests result)
IR illuminator support:	ICR - Movable InfraRed filter
S/N ratio:	> 50 dB
Video output:	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω

Main features:	<ul style="list-style-type: none">• 2D-DNR - Digital Noise Reduction• BLC - configurable Back Light Compensation• HLC - High Light Compensation (spot)• D-WDR - Wide Dynamic Range• AGC - Automatic Gain Control• Mirror - Mirror image• Auto White Balance
OSD menu:	✓, OSD menu available via recorder
Power supply:	12 V DC / 230 mA
Power consumption:	≤ 2.8 W
Housing:	Dome, Plastic
Vandal-proof:	—
Color:	White
Operation temp:	-40 °C ... 60 °C
Weight:	0.100 kg
Dimensions:	Ø 85 x 69 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years