

Code: PCC-60K9

SWITCHING ADAPTER **PCC-60K9**

The power supply adapter has an aesthetic, solid metal box. It allows to connect up to 9 cameras with max. current consumption of 500mA for each output. The power adapter is designed to small surveillance systems based on standard DVR. It allows user to control each camera circuit.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current. Please pay attention for proper cooling conditions of the power adaptor during work!



Adapter type:	Switching
Number of outputs:	9
Output voltage:	12 V DC
Output voltage adjustment:	10.8 ... 13.2 V
Max. output current (total):	4.5 A
Max. output current for single output:	0.5 A
LED indication:	✓
Input voltage:	100 ... 240 V AC
Voltage frequency range:	50 ... 60 Hz
Power:	54 W
Connector type:	Cable terminals
Housing type:	Metal, wall-mounted
Protection class:	class I
Overload protection:	✓



DATA SHEET

Overvoltage protection:	✓
Short-circuit protection:	✓
Key closed:	✓
Operation temp. / Relative humidity:	0 °C ... 50 °C / 20 % ... 90 %
Weight:	1.3 kg
Dimensions:	235 x 205 x 50 mm
Guarantee:	1 year