

Code: DH-IPC-EB5500P

IP VANDALPROOF CAMERA **DH-IPC-EB5500P** - 5.0 Mpx 1.42 mm - Fish Eye DAHUA

IP camera with "fish eye" wide-angle lens.
PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	5.0 Mpx
Scanning system:	Progressive
Resolution:	2560 x 1920 - 5.0 Mpx , 2048 x 1536 - 3.0 Mpx , 1600 x 1200 - UXGA , 1280 x 960 - 1.3 Mpx
Lens:	1.42 mm - Fish Eye / F2.6
View angle:	185 °
S/N ratio:	> 50 dB
RS-485 interface:	—
Image compression method:	H.264 / MJPEG
Alarm inputs / outputs:	1 / 1
Audio:	<ul style="list-style-type: none"> • Microphone built-in • External microphone input • Audio output • Bi-directional audio streaming support
Bitrate:	20 ... 8192 kbps H.264
Main stream frame rate:	12 fps @ 5 Mpx 20 fps @ 3 Mpx 25 fps @ 1600 x 1200





DATA SHEET

Network interface:	10/100 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Memory card slot:	Micro SD memory cards up to 64GB support (possible local recording)
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application DMSS• iOS (iPhone): Free application DMSS
Default admin user / password:	admin / admin
Default IP address:	192.168.1.108
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	2.41
Main features:	<ul style="list-style-type: none">• Heat map - the selection in the image by corresponding colors the areas with different traffic• 3D-DNR - Digital Noise Reduction• Possibility to change the resolution, quality and bit rate• Time mark and image description• Image rotation and mirror• Configurable: brightness, contrast, saturation• Privacy zones• Motion Detection
Vandal-proof:	✓
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 480 mA
Power consumption:	≤ 6 W
Housing:	Dome - Metal
Color:	White
Operation temp:	-30 °C ... 60 °C
"Index of Protection":	IP66
Weight:	0.284 kg
Dimensions:	Ø 110 x 54 mm
Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA



DATA SHEET

Guarantee:

3 years