

Code: GT-N78-6464

NVR **GT-N78-6464** 64 CHANNELS +eSATA GEMINI TECHNOLOGY



| | |
|-------------------------------------|---|
| Standard: | TCP/IP |
| Supported resolutions: | 64 @ 4096 x 2160 px, 64 @ 2592 x 1944 px, 64 @ 2048 x 1536 px, 64 @ 1920 x 1080 px, 64 @ 1280 x 960 px |
| Video outputs: | 1 pcs HDMI 1 pcs VGA |
| Audio support: | 64 Channels |
| Audio inputs: | Audio from cameras |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265 / H.264 |
| Maximal total frame rate: | 1600 fps @ 4096 x 2160 px, 1600 fps @ 2592 x 1920 px, 1600 fps @ 2048 x 1536 px, 1600 fps @ 1920 x 1080 px, 1600 fps @ 1280 x 960 px, |
| Supported hard drives: | 8 x 6 TB SATA + 1 x eSATA - The ability to limit a disk space - quota |
| Recording modes: | Manual, Sensor, Motion detection, Schedule |
| Image analysis: | Virtual Guard, abandoned/missing object, intrusion |
| Network protocols: | ONVIF, I8, I8H, I9, RTSP |
| External storage devices backup: | Records backup at .i8 / .avi format to USB (pendrive) |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow |
| Bitrate: | max. 512 Mbps |



DATA SHEET

| | |
|----------------------------------|---|
| Network functions: | Network client and browser software IE, Firefox, Opera, Chrome: live view, playback and backup of the records and configuration of the recorder parameters |
| Operation temp: | -10 °C ... 55 °C |
| ONVIF: | ✓ |
| Mobile phones support: | Port no.: 5800 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application Fseye• iOS: Free application Fseye |
| Default IP address: | 192.168.1.189 |
| Default admin user / password: | admin / 888888 |
| Web browser access ports: | 80, 554 - Internet Explorer 80, 1935 - Chrome, Firefox, Opera |
| PC client access ports: | 5050, 5051, 5052 |
| Mobile client access ports: | 5800 |
| RTSP URL: | rtsp://ip_address:554/ch01.264 - Main stream, first channel rtsp://ip_address:554/ch01_sub.264 - Sub stream, first channel |
| Alarm inputs / outputs: | 4 / 4 |
| PTZ control: | RS-485 - PELCO-D/P |
| Motion Detection: | 22 x 18 motion zones |
| Mouse support: | ✓ |
| IR remote controller in the set: | — |
| Power supply: | 230 V AC |
| Weight: | 7.68 kg |
| Dimensions: | 480 x 480 x 98 mm 2 U Rack 19" |
| Supported languages: | English, Polish |
| Country of origin: | China |
| Manufacturer / Brand: | GEMINI TECHNOLOGY |
| Guarantee: | 2 years |

