

Code: DHI-NKB3000

IP / RS-485 KEYBOARD CONTROLLER **DHI-NKB3000** DAHUA

Network keyboard with full possibilities of controlling and programming the PTZ camera heads of the DH-SD series. It is also possible to control many DVRs from one keyboard.



Protocols:	DH-SD, Pelco-P, Pelco-D, PELCO-P1, PELCO-D1 and others
Cameras numbers (ID):	1 ... 255
Maximal control distance:	1200 m @ RS-485 / RS-232
Users + admins:	20 + 1
Connectors:	<ul style="list-style-type: none"> • RS-422 - cable terminals • RS-485 - cable terminals • RS-232 - 15 pin • RJ-45 - Gigabit Ethernet • VGA (D-Sub 15-pin) • 2 x USB 2.0 • HDMI • 2 x Jack 3.5 mm socket - Headphones output, External microphone input
Communication standard:	<ul style="list-style-type: none"> • Network mode - Gigabit Ethernet, RJ-45 socket • Network mode - Wi-Fi • Direct mode - RS-485, terminals • Direct mode - RS-422, terminals • Direct mode - RS-232, D-sub socket
Manipulator:	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)
Display:	10.2 " LCD - 800 x 480 px, capacitive touch screen, with light indication
Video output:	1 x HDMI 1 x VGA
PTZ control:	<ul style="list-style-type: none"> • Dahua or other manufacturers Speed Dome cameras • Recorders DAHUA
Operation modes:	<ul style="list-style-type: none"> • Normal mode • Matrix mode • Platform mode

Main features:	<ul style="list-style-type: none">• Backup to USB drive (pendrive, external drive)• Live view up to 16 cameras with resolution up to 1080p• Bi-directional audio streaming support• Keypad backlight buttons• Split screen at view from cameras : 1 / 4 / 8 / 9 / 16• Graphical menu - touch control and by using the buttons . Mouse support
Power supply:	12 V DC / 3 A
Operation temp. / Relative humidity:	-10 °C ... 55 °C / max. 90 % non-condensing
Weight:	2.92 kg
Dimensions:	480 x 240 x 135 mm
Supported languages:	English, Polish
Manufacturer / Brand:	DAHUA
Guarantee:	3 years