

Code: UT2200E-FR/UPS

UPS **UT2200E-FR/UPS** 2200 VA CyberPower

The UT2200E-FR/UPS UPS is a professional device used to maintain the operation of the components connected to it. The UPS UT CyberPower series has been equipped with the best-in-class housing of fireproof plastic, which provides outstanding fire resistance and helps to minimize possible losses in the case of fire.



Nominal power:	1320 W
Apparent Power:	2200 VA
Input voltage:	165 V ... 290 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Transfer time:	4 ms
Typical battery charge time:	8 hours
Battery:	2 pcs RBP0090 9 Ah
Estimated battery operation time:	• 95 minutes @ 60 W, • 70 minutes @ 90 W, • 34 minutes @ 200 W
Number of outputs:	4 pcs
Protections:	• Overvoltage • Overload protection • Overcharge protection • Protection: DSL / Tel / FAX / Modem - RJ11 / RJ45

Operation state indication:	• LED diodes, • Sound signaling
Main features:	• Automatic Voltage Regulator (AVR) • Compatible with power generators • Battery Managment Technology - Increased battery life • Fireproof housing • Built-in EMI, RFI filter • Configurable alarm
Application:	• Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	10.63 kg
Dimensions:	298 x 178 x 148 mm
Manufacturer / Brand:	CyberPower
Guarantee:	2 years