

Code: BCS-NVR04015ME-P-II

## NVR **BCS-NVR04015ME-P-II** 4 CHANNELS, 4 PoE



|                                  |  |
|----------------------------------|--|
| Standard:                        | TCP/IP   |
| Supported resolutions:           | 4 @ 3840 x 2160 px,<br>4 @ 3072 x 2048 px,<br>4 @ 2560 x 1920 px,<br>4 @ 2688 x 1520 px,<br>4 @ 2048 x 1536 px,<br>4 @ 1920 x 1080 px,<br>4 @ 1280 x 720 px,   |
| Video outputs:                   | 1 pcs HDMI 4K<br>1 pcs VGA   |
| Audio support:                   | 4 Channels - Audio from cameras, Bi-directional audio streaming support  |
| Audio inputs:                    | 1 pcs CINCH  |
| Audio outputs:                   | 1 pcs CINCH  |
| Image compression method:        | H.265 / H.264 / MJPEG  |
| Maximal total frame rate:        | 100 fps @ 3840 x 2160 px,<br>100 fps @ 3072 x 2048 px,<br>100 fps @ 2560 x 1920 px,<br>100 fps @ 2688 x 1520 px,<br>100 fps @ 2048 x 1536 px,<br>100 fps @ 1920 x 1080 px,<br>100 fps @ 1280 x 720 px, |
| Supported hard drives:           | 1 x 6 TB SATA III  |
| Recording modes:                 | Manual, Motion Detection, Schedule   |
| Network protocols:               | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, IP Filter, PPPoE, FTP, IP Search, Lechange, ONVIF 2.4   |
| External storage devices backup: | Backup to USB drive (pendrive, external drive)   |



# DATA SHEET

|                                     |  |
|-------------------------------------|--|
| Default admin user / password:      | admin / admin  |
| Default IP address:                 | 192.168.1.108  |
| Web browser access ports:           | 80, 37777  |
| PC client access ports:             | 37777  |
| Mobile client access ports:         | 37777  |
| RTSP URL:                           | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                            |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function |
| Bitrate:                            | max. 80 Mbps   |
| Intelligent image analysis:         | ✓  |
| Network functions:                  | Full support via network, Remote records copying, Web-Server built-in<br>max. 128 on-line users  |
| ONVIF:                              | 2.4  |
| Switch PoE:                         | 4-port PoE Switch built-in, PoE (802.3af/at)   |
| Operation temp:                     | -10 °C ... 50 °C   |
| Mobile phones support:              | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">DMSS</a><br>• iOS (iPhone): Free application <a href="#">DMSS</a>  |
| Alarm inputs / outputs:             | —  |
| PTZ control:                        | IP Speed Dome Cameras  |
| Motion Detection:                   | 22 x 18 motion zones   |
| Mouse support:                      | ✓  |
| IR remote controller in the set:    | —  |
| Power supply:                       | 48 V DC / 1.5 A (power adapter included)   |
| Weight:                             | 0.5 kg   |
| Dimensions:                         | 240 x 205 x 44 mm  |
| Supported languages:                | English, Polish  |
| Country of origin:                  | China  |
| Manufacturer / Brand:               | BCS  |
| Guarantee:                          | <b>3 years</b>   |