

Code: PRT66EM-G

PROXIMITY READER **PRT66EM-G** ROGER

Indoor proximity cards and key-fobs reader. Unique 125 kHz standard.



Cards support:	Unique EM 125kHz
Reading distance of prox-keys:	max. 15 cm
Keyboard built-in:	—
Communication:	<ul style="list-style-type: none"> • Wiegand 26-66bit • Magstripe (Clock & Data) • RS-232 • RACS (Roger)
Main features:	<ul style="list-style-type: none"> • Autonomous operation or as terminal for the controller • Can be used for EMC-4 card programming (free of charge RARC software is required) • Tamper protection (detection of removing from mounting surface and enclosure opening) • Manual or computer programming
Selected features of the standalone mode:	<ul style="list-style-type: none"> • 120 indexed users • History of 1024 events • Support for door contact and exit button • Two way door control (requires using two readers of PRT series) • Operation with XM-2 I/O extension module (Full Standalone Mode)
Power supply:	10 ... 15 V DC
Average current consumption:	45 mA



DATA SHEET

Operation temp:	-25 °C ... 60 °C
Permissible relative humidity:	10 ... 95 % (non-condensing)
Weight:	0.15 kg
Dimensions:	85 x 85 x 27 mm
Manufacturer / Brand:	ROGER
Guarantee:	3 years