

Code: DHI-XVR8808S

HD-CVI, PAL, TCP/IP DVR **DHI-XVR8808S** 8 CHANNELS +eSATA DAHUA

The DHI-XVR8808S digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs:	8 pcs BNC - AHD / HD-CVI / HD-TVI / PAL
Video outputs:	<ul style="list-style-type: none"> • 2 pcs HDMI • 1 pcs VGA • 1 pcs CVBS - BNC socket • 8 pcs - BNC socket (Loop through) - HD-CVI / CVBS only
Audio inputs:	8 pcs BNC 1 pcs BNC - External microphone input
Audio outputs:	2 pcs BNC
Maximal total frame rate:	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI / PAL : 120 fps @ 2560 x 1440 px - HD-CVI only 200 fps @ 1920 x 1080 px, 200 fps @ 1280 x 720 px, 200 fps @ 960 x 576 px, 200 fps @ 720 x 576 px, 200 fps @ 352 x 288 px, • IP : 1600 fps @ max. 4000 x 3000 px
Recording speed adjustment:	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI / PAL : 1 ... 15 fps @ 2560 x 1440 - HD-CVI only 1 ... 25 fps @ 1920 x 1080 1 ... 25 fps @ 1280 x 720 1 ... 25 fps @ 960 x 576 1 ... 25 fps @ 720 x 576 1 ... 25 fps @ 352 x 288 for each channel • IP 1 ... 25 fps @ max. 12 Mpx for each channel





DATA SHEET

Operation modes:	<ul style="list-style-type: none">• 8 x AHD / HD-TVI @ 1080p / HD-CVI @ 3.7 Mpx• 7 x AHD / HD-TVI @ 1080p / HD-CVI @ 3.7 Mpx + 1 x IP @ 12 Mpx• 6 x AHD / HD-TVI @ 1080p / HD-CVI @ 3.7 Mpx + 2 x IP @ 12 Mpx• 5 x AHD / HD-TVI @ 1080p / HD-CVI @ 3.7 Mpx + 3 x IP @ 12 Mpx• 4 x AHD / HD-TVI @ 1080p / HD-CVI @ 3.7 Mpx + 4 x IP @ 12 Mpx• 3 x AHD / HD-TVI @ 1080p / HD-CVI @ 3.7 Mpx + 5 x IP @ 12 Mpx• 2 x AHD / HD-TVI @ 1080p / HD-CVI @ 3.7 Mpx + 6 x IP @ 12 Mpx• 1 x AHD / HD-TVI @ 1080p / HD-CVI @ 3.7 Mpx + 7 x IP @ 12 Mpx• 8 x AHD / HD-TVI @ 1080p / HD-CVI @ 3.7 Mpx / IP @ 12 Mpx + 56 x IP @ 12 Mpx All modes allow for any combination of the AHD-H, HD-CVI, HD-TVI, PAL cameras
Image compression method:	H.264 / H.264+
Number of compression levels:	4
Image records resolutions:	2560 x 1440 - HD-CVI only 1920 x 1080 1280 x 720 960 x 576 720 x 576 352 x 288 max. 4000 x 3000 - IP
Recording modes:	Manual, Sensor, Motion detection, Schedule
Supported hard drives:	8 x 8 TB SATA + eSATA
External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Alarm inputs / outputs:	16 / 6
PTZ control:	<ul style="list-style-type: none">• IP Speed Dome Cameras• Control compatible with coax PTZ HD-CVI• RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones 22 x 18 motion zones Very good sensitivity after motion detection records detected channels only
Main features:	Intelligent image analysis : intrusion, crossing the line (tripwire), abandoned/missing object, face detection, people counting
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	230 V AC
Weight:	6.98 kg
Dimensions:	440 x 455 x 95 mm
Supported languages:	English, Bulgarian, Czech, Finnish, Greek, Polish, Romanian, Serbian, Slovenian, Hungarian
Country of origin:	China



DATA SHEET

Manufacturer / Brand:	DAHUA
Guarantee:	3 years

