

Code: GT-CI12C5-28VF

## IP CAMERA **GT-CI12C5-28VF** - 720p 2.8 ... 12 mm GEMINI TECHNOLOGY

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 720p.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).



|                                  |                                                                            |
|----------------------------------|----------------------------------------------------------------------------|
| Standard:                        | TCP/IP                                                                     |
| Sensor:                          | 1/2.7 " Brigates BG0703 CMOS                                               |
| Digital Image Processor:         | Hisilicon 3518E V200                                                       |
| Matrix size:                     | 1.0 Mpx                                                                    |
| Resolution:                      | 1280 x 720 - 720p<br>640 x 480 - VGA<br>640 x 360 - Q720p                  |
| Lens:                            | 2.8 ... 12 mm                                                              |
| View angle:                      | • 88 ° ... 25 ° (manufacturer data)<br>• 100 ° ... 34 ° (our tests result) |
| S/N ratio:                       | > 50 dB                                                                    |
| Range of IR illumination:        | 50 m                                                                       |
| IR illuminator power adjustment: | By potentiometer                                                           |
| Image compression method:        | H.264                                                                      |
| Alarm inputs / outputs:          | —                                                                          |
| Bitrate:                         | 16 ... 8000 kbps                                                           |
| Main stream frame rate:          | max. 25 fps - 720p                                                         |
| Network interface:               | 10/100 Base-T (RJ-45)                                                      |



# DATA SHEET

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network protocols:             | TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, NTP, PPPoE, UPnP, SMTP                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Audio:                         | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Mobile phones support:         | Port no.: 5800 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">Fseye</a></li><li>• iOS: Free application <a href="#">Fseye</a></li></ul>                                                                                                                                                                                                                                                                                                                                                              |
| Default IP address:            | 192.168.1.188                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Default admin user / password: | admin / (null)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Web browser access ports:      | 80, 554, 1935                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| PC client access ports:        | 5050, 5051, 5052                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| WEB Server:                    | Built-in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Mobile client access ports:    | 5800                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Max. number of on-line users:  | 10                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| ONVIF:                         | 2.21                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| RTSP URL:                      | rtsp://ip_address:554/ch01.264 - Main stream<br>rtsp://ip_address:554/ch01_sub.264 - Sub stream                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| RS-485 interface:              | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Main features:                 | <ul style="list-style-type: none"><li>• 3D-DNR - Digital Noise Reduction</li><li>• WDR - Wide Dynamic Range</li><li>• ICR - Movable InfraRed filter</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• Time mark and image description</li><li>• Image rotation and mirror</li><li>• Configurable: brightness, contrast, saturation</li><li>• Day/Night mode - configurable</li><li>• Possibility to add different privileges to the users</li><li>• Privacy zones - max. 4</li><li>• Sharpness - sharper image outlines</li></ul> |
| Power supply:                  | 12 V DC / 420 mA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Power consumption:             | ≤ 5.0 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Housing:                       | Compact, Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Color:                         | Graphite                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| "Index of Protection":         | IP67                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Supported languages:           | English, Polish                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Operation temp:                | -20 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Weight:                        | 0.82 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Dimensions:                    | 260 x 123 x 92 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Manufacturer / Brand:          | GEMINI TECHNOLOGY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Guarantee:                     | 2 years                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |