

Code: BCS-P-NVR0801-4K-8P

## NVR **BCS-P-NVR0801-4K-8P** 8 CHANNELS +8-PORT SWITCH POE, 4K UHD BCS POINT



|                                     |                                                                                                                                                                                                            |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                     |
| Supported resolutions:              | max. 8.3 Mpx - 3840 x 2160 px, 4K UHD                                                                                                                                                                      |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA                                                                                                                                                                                 |
| Audio support:                      | 8 Channels - Audio from cameras                                                                                                                                                                            |
| Audio inputs:                       | 1 pcs CINCH - External microphone input                                                                                                                                                                    |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                                                |
| Image compression method:           | H.265, H.264                                                                                                                                                                                               |
| USB:                                | 3 pcs USB 2.0                                                                                                                                                                                              |
| Supported hard drives:              | 1 x 6 TB SATA                                                                                                                                                                                              |
| Recording modes:                    | Manual, Sensor, Motion detection, Schedule                                                                                                                                                                 |
| Network protocols:                  | HTTP, TCP/IP, IPv4, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, IP Filter, PPPoE, FTP, IP Server, P2P                                                                                                     |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                                             |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function |
| Bitrate:                            | max. 60 Mbps                                                                                                                                                                                               |
| Network functions:                  | Full support via network, Remote records copying, Web Server built-in<br>max. 128 on-line users                                                                                                            |
| ONVIF:                              | 2.4                                                                                                                                                                                                        |



# DATA SHEET

|                                  |                                                                                                                                                                                                                  |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mobile phones support:           | Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">BCS Point</a></li><li>• iOS (iPhone): Free application <a href="#">BCS Point</a></li></ul> |
| Default admin user / password:   | admin / 123456                                                                                                                                                                                                   |
| Default IP address:              | DHCP                                                                                                                                                                                                             |
| Web browser access ports:        | 80, 554                                                                                                                                                                                                          |
| PC client access ports:          | 80                                                                                                                                                                                                               |
| Switch PoE:                      | 8-port PoE Switch built-in, 25.5 W / Channel, PoE (802.3af/at)                                                                                                                                                   |
| Mobile client access ports:      | 80                                                                                                                                                                                                               |
| RTSP URL:                        | rtsp://192.168.1.66:554/unicast/c1/s0/live - Main stream<br>rtsp://192.168.1.66:554/unicast/c1/s1/live - Sub stream                                                                                              |
| Alarm inputs / outputs:          | 4 / 1                                                                                                                                                                                                            |
| PTZ control:                     | IP Speed Dome Cameras                                                                                                                                                                                            |
| Motion Detection:                | 22 x 18 motion zones - after motion detection records detected channels only                                                                                                                                     |
| Intelligent image analysis:      | —                                                                                                                                                                                                                |
| Mouse support:                   | ✓                                                                                                                                                                                                                |
| IR remote controller in the set: | ✓                                                                                                                                                                                                                |
| Power supply:                    | 52 V DC / 1.8 A (power adapter included)                                                                                                                                                                         |
| Weight:                          | 1.1 kg                                                                                                                                                                                                           |
| Dimensions:                      | 261 x 247 x 46 mm                                                                                                                                                                                                |
| Supported languages:             | English, German, Polish, Russian, Slovak                                                                                                                                                                         |
| Country of origin:               | China                                                                                                                                                                                                            |
| Manufacturer / Brand:            | BCS POINT                                                                                                                                                                                                        |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                                                                   |