

Code: DH-HAC-PFW3601P-A180

HD-CVI VANDALPROOF CAMERA **DH-HAC-PFW3601P-A180** PANORAMIC - 8.3 Mpx, 4K UHD 3 X 3.6 mm DAHUA

The HD-CVI camera is equipped with 3 high quality image sensors and 3 lenses with 3.6 mm focal length. Thanks to its unique design, the camera has a 180° viewing angle.

Camera is according to IP67 Index of Protection norm. The 3-Axis integrated camera bracket has a regulation in all three planes, which allows to turn the camera to any direction. Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.



| | |
|----------------------------------|--|
| Standard: | HD-CVI |
| Sensor: | 3 x 1/2.8 " STARVIS™ CMOS |
| Matrix size: | 3 x 2.1 Mpx |
| Resolution: | 3840 x 2160 - 8.3 Mpx, 4K UHD @ 15 fps , 2560 x 1440 - 3.7 Mpx @ 25 fps |
| Video output: | 1 pcs HD-CVI - 4K UHD - A panoramic image 3 pcs HD-CVI - 1080p |
| Lens: | 3 x 3.6 mm / F1.8 |
| View angle: | 180 ° |
| S/N ratio: | > 65 dB |
| Range of IR illumination: | 20 m |
| IR illuminator power adjustment: | Automatic |
| Audio: | External microphone input - Jack 3.5 mm socket |
| Alarm inputs / outputs: | 2 / 1 |
| OSD menu: | ✓ |

| | |
|------------------------|---|
| Main features: | <ul style="list-style-type: none">• WDR - 120 dB - Wide Dynamic Range• 2D-DNR, 3D-DNR - Digital Noise Reduction• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• ICR - Movable InfraRed filter• AGC - Automatic Gain Control• Auto White Balance• Motion Detection• Configurable: brightness, contrast, saturation |
| Power supply: | 12 V DC / 1830 mA |
| Power consumption: | ≤ 22 W |
| Housing: | Compact, Aluminum |
| Color: | White / Black |
| "Index of Protection": | IP67 |
| Vandal-proof: | IK10 |
| Operation temp: | -30 °C ... 60 °C |
| Weight: | 1.98 kg |
| Dimensions: | 286 x 119 x 106 mm |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 5 years |