

Code: AT-UPS650P-LED

## UPS **AT-UPS650P-LED** 650 VA EAST

The AT-UPS650P-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device works with power supply adapters having Active Power Factor Correction (APFC).



|                                          |                                                                                                                                  |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Nominal power:                           | 390 W                                                                                                                            |
| Apparent Power:                          | 650 VA                                                                                                                           |
| Input voltage:                           | 165 V ... 275 V AC                                                                                                               |
| Input frequency:                         | 50 / 60 Hz (auto detection)                                                                                                      |
| Output voltage:                          | 230 V AC $\pm$ 10 % (Approximated Sine Wave)                                                                                     |
| Output frequency:                        | 50 / 60 Hz $\pm$ 1 %                                                                                                             |
| Transfer time:                           | $\leq$ 10 ms                                                                                                                     |
| Charging time (recover to 90% capacity): | 8 hours                                                                                                                          |
| Battery:                                 | 1 pcs - 12V/7Ah                                                                                                                  |
| Estimated battery operation time:        | <ul style="list-style-type: none"> <li>• 17 minutes @ 100 W</li> <li>• 6 minutes @ 200 W</li> <li>• 2 minutes @ 300 W</li> </ul> |
| Number of outputs:                       | 4 pcs CEE 7/3 (Schuko)                                                                                                           |

|                                      |                                                                                                                                                                                                                                                           |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protections:                         | <ul style="list-style-type: none"><li>• Glass Fuse</li><li>• Overvoltage</li><li>• Overload protection</li><li>• Overcharge protection</li><li>• Telephone line filter</li></ul>                                                                          |
| Operation state indication:          | <ul style="list-style-type: none"><li>• LED diodes,</li><li>• Sound signaling</li></ul>                                                                                                                                                                   |
| Main features:                       | <ul style="list-style-type: none"><li>• Automatic Voltage Regulator (AVR)</li><li>• Compatible with power generators</li><li>• Remote management - UPSmart application included</li><li>• Built-in EMI, RFI filter</li><li>• Configurable alarm</li></ul> |
| Application:                         | <ul style="list-style-type: none"><li>• Surveillance Systems</li><li>• data storage centers</li><li>• network, servers, workstations</li><li>• Industrial Equipment</li></ul>                                                                             |
| Housing type:                        | Desktop                                                                                                                                                                                                                                                   |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 20 ... 90 %                                                                                                                                                                                                                              |
| Weight:                              | 4.49 kg                                                                                                                                                                                                                                                   |
| Dimensions:                          | 280 x 185 x 95 mm                                                                                                                                                                                                                                         |
| Manufacturer / Brand:                | EAST                                                                                                                                                                                                                                                      |
| Guarantee:                           | 2 years                                                                                                                                                                                                                                                   |