

Code: APTI-33V3-2812WP

IP VANDALPROOF CAMERA **APTI-33V3-2812WP** - 3.0 Mpx 2.8 ... 12 mm

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 2048 x 1536 (3 Mpx).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	1/2.8 " Sony CMOS IMX123
Digital Image Processor:	Hisilicon 3516D
Matrix size:	3.0 Mpx
Resolution:	2304 x 1296 - 3.0 Mpx , 1920 x 1080 - 1080p ,
Lens:	2.8 ... 12 mm, 5 Mpx
View angle:	<ul style="list-style-type: none"> • 85 ° ... 23 ° (manufacturer data) • 80 ° ... 30 ° (our tests result)
S/N ratio:	> 52 dB
Range of IR illumination:	30 m
Memory card slot:	—
Image compression method:	H.265 / H.264 / MJPEG
Bitrate:	64 ... 12000 kbps



DATA SHEET

Main stream frame rate:	<ul style="list-style-type: none">• 20 fps @ 3.7 Mpx• 30 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45)
Alarm inputs / outputs:	—
Audio:	—
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
WEB Server:	Built-in
Max. number of on-line users:	3
ONVIF:	2.4
RS-485 interface:	—
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application FREEIP• iOS (iPhone): Free application FREEIP
Default IP address:	192.168.1.168
Default admin user / password:	admin / admin
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Main features:	<ul style="list-style-type: none">• 3D-DNR - Digital Noise Reduction• WDR - Wide Dynamic Range• F-DNR (Defog) - Reduction of image noise caused by precipitation• HDR (High Dynamic Range) - the wide range of light dynamics provides a very good distinguishing of details on both the light and the dark areas of the image• RESET button - on the cable• ICR - Movable InfraRed filter• Possibility to change the resolution, quality and bit rate• Motion Detection• Privacy zones• Configurable: brightness, contrast, saturation• Sharpness - sharper image outlines• Mirror - Mirror image
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 560 mA
Power consumption:	≤ 6.7 W
Housing:	Dome - Metal
Vandal-proof:	✓
Color:	White
"Index of Protection":	IP66
Operation temp:	-20 °C ... 55 °C



DATA SHEET

Weight:	0.59 kg
Dimensions:	Ø 120 x 95 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years